

The Opening Rooflight By Rooflight Solutions

Detailed Description

Features:

Grade 6063-T6 Extruded Aluminium
Fully Thermally Broken
Polyester Powder Coating to Minimum 60 Microns

Suitable for Marine / Coastal Environments
Stainless Steel Concealed Fixings
Tested in accordance with the CWCT Standard
Air & Water Resistance 1050pa
Wind Load Resistance 2.0kN/m²



Usage:

Suitable for all nominally flat roof constructions and coverings e.g. Single Ply PVC, Fiberglass, lead, copper, zinc and other standing seams and asphaltic material.

Suitable for Green / Sedum Roofs

Product Guidance

As Standard:

Stock / Standard Sizes (Non-standard sizes and shapes are available on request)

(mm)	Height	1000	1200	1400
Width				
1000		✓	✓	✓
1200		✓	✓	✓
1400		✓	✓	✓
1700		✓	✓	✓
2200		✓	✓	✓

NB: These are external kerb sizes.

Internal finished sizes; minus 200mm from above Width & Height dimensions

Glazing Details:

6mm Toughened Outer
20 mm Warm Edge Spacer with 90% Argon Cavity
6mm Toughened Low-e Inner

Glass Centre Pane U-Value 1.1W/m²K

Colour:

Internal – Ral 9010 Mat
External – Ral 7015 Mat

Seals:

Structural & Weather Seal – Low Modulus Silicone Sealant
EPDM – UV & Water Resistant

Upstand:

To suit an overall finished Upstand of 100mm.

Warranty:

1 Year offered as standard.
Extended warranty available as below, upon registration.

Glazing 10 Years
Powder Coating 10 Years
Mechanical Components 1 Year

Options

Operation:

Manual or Electric, Wind, Rain & Temperature Sensors for auto-closing. Remote Control

Size:

Non-standard sizes and shapes are available on request.

Colour:

Any RAL or BS colour can be specified
Anodised options

Glazing Details:

Enhanced glazing specifications incorporating thermal, acoustic, security, light transmission, solar gain and decorative options are available, please contact manufacturer for details.

Frame Material:

Different material specifications stainless steel cladding etc are available please contact manufacturer for details.

Product Specification

Manufacturer:

Name: Rooflight Solutions Ltd
Web: www.rooflightsolutions.co.uk
Email: sales@rooflightsolutions.co.uk
Tel: +44 (0)800 999 7774
Address: Rooflight Solutions LTD, 44 Berry Street, Wolverhampton, WV1 1HA
Product reference: The Opening Rooflight

Other Rooflights in the Range

Fixed Rooflight
Access Hatch Roof Window – Manual
Access Hatch Roof Window – Electric
Walk On Floorlight – (Internal Use)
Walk On Rooflight – (External Use)
Pyramid Rooflight
Pyramid Rooflight – Manual
Pyramid Rooflight - Electric
Lantern Rooflight
Lantern Rooflight - Manual
Lantern Rooflight - Electric